


INSTALLATION AND WIRING DIAGRAM

USA

LEDRA SERIES LEDS

LEDRA™ AL-J

| | | | | |
|----------|-------------|--------------------------|-----------|--------------------|
| ART. NO. | 135 341/f | frosted, LED white 5000K | 135 343/f | frosted, LED green |
| | 135 341-1/f | frosted, LED white 3000K | 135 344/f | frosted, LED red |
| | 135 342/f | frosted, LED blue | 135 345/f | frosted, LED amber |



IMPORTANT SAFETY INSTRUCTIONS



1. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH LOCAL NEC CODE.
2. WET LOCATION SUITABLE.
3. SUITABLE FOR SUSPENDED CEILING.
4. **FOR WET LOCATION INSTALLATION, FIXTURE MUST BE SURFACE MOUNTED OVER A RECESSED JUNCTION BOX (MAX DIAMETER 3 1/2")**
5. **WHEN MOUNTING ONTO UNEVEN SURFACES, SILICONE MUST BE APPLIED IN BETWEEN THE CANOPY HOUSING AND THE SURFACE TO PREVENT WATER INFILTRATION.**
6. Turn off power prior to any work on the systems.
7. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE FIXTURE

Contents of Delivery: LEDRA AL-J - qty. (1)

Note: Fixture must be mounted over a standard junction box

- Begin by connecting the feed wire (A) through gasket (G) from the transformer to the power cables in the wall.

- Insert the mounting screw (C) into the mounting plate (B).

- Align the mounting screws (C) through gasket with the J-box and tighten until firmly connected.

- Connect male and female quick connect (F) then place the LEDRA AL-J (D) over the mounting plate (B) and secure with the allen screws (E) located on the side of the base.

