


INSTALLATION INSTRUCTIONS

USA

TECHNICAL

POWER FEED COVER I

ART. NO.	240 100bz	bronze
	240 100ch	chrome
	240 100mc	matte chrome



IMPORTANT SAFETY INSTRUCTIONS



1. Read all instructions!
2. Turn off power prior to any work on the canopy.
3. Turn off power prior to adding or changing the configuration of the track.
4. Do not install this track in a damp or wet location
5. Only BRUCK Flex-line system components may be used for assembly of this system.
6. Only BRUCK fixtures and components may be mounted on the system
7. Never connect the system and lamps directly to the main power source without the use of a transformer. This system must be used in conjunction with low voltage, 12V transformer.
8. Total wattage of the system must never exceed the wattage supplied by the low voltage transformers. BRUCK recommends an average load of 250W for a 300W transformer.
9. CAUTION! Lamps and fixtures become hot during operation
10. Observe the stated minimum distance of the illuminants to flammable objects.
11. Do not install the track or any part which contains exposed wires less than 7 ft. from the floor.
12. Do not hang any objects over the system; short circuit and fire hazard.
13. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE SYSTEM

This Package Contains:

Power Feed Cover I - qty.(1)

A. Thread power supply cable through ceiling and through mounting plate. Tighten mounting plate to ceiling with screws.

B. Thread power supply cable and copper High-Line cable through canopy.

C. Run power supply cable through feed pipe. The rod is held in place with allen screw.

D. Place canopy over mounting plate and secure with allen screw.

E. Cut remaining power supply cable, leave 2 - 3" of cable at the end of the rod to attach to a power feed.

SHORTENING THE SUPPORT ROD

1. Remove the rod by unscrewing the allen on the metal sleeve.
2. Cut the rod to the desired length.
3. Reinsert the rod into the metal sleeve and tighten the allen screw.

