


INSTALLATION INSTRUCTIONS

USA

TECHNICAL

4" SURFACE MOUNT CANOPY 150

Art. No.	240 201bz	bronze, 150W
	240 201ch	chrome, 150W
	240 201mc	matte chrome, 150W



IMPORTANT SAFETY INSTRUCTIONS



1. Read all instructions!
2. Turn off power prior to any work on the canopy.
3. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE.
4. This surface canopy MUST BE HARD WIRED, 120v. For all the wire connections, use Listed Wire Nuts.
5. Only BRUCK track systems may be used with the surface canopy.
6. Total wattage of the track must never exceed the wattage supplied by the low voltage electronic transformer. Please check that the total lamp wattage does not exceed 150W.
7. Secondary connections must be clean and tight to avoid arcing and overheating!
8. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE SYSTEM

This Package Contains:

4" Surface Mount Canopy - qty.(1)

The 4" Surface Mount Canopy 150 can be mounted directly to any ceiling with access to the power cables.

- Begin by connecting the three wires line, common, and ground from the transformer (A) to the power cables in the wall.
- Screw (B) mounting plate into surface with mounting screws.
- Tighten the side screws (C) to complete installation.
- Follow instructions provided in power feed kits to complete installation.

