


INSTALLATION INSTRUCTIONS

USA

TECHNICAL

EXTENSION RING

Art. No.	80159bz	bronze
	80159ch	chrome
	80159mc	matte chrome



IMPORTANT SAFETY INSTRUCTIONS



1. Read all instructions!
2. Turn off power prior to any work on the canopy.
3. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE.
4. MUST BE HARD WIRED, 120v. For all the wire connections, use Listed Wire Nuts.
5. Only BRUCK Uni-Light fixtures may be used with the surface canopy.
6. Total wattage of the fixture must never exceed the wattage supplied by the low voltage electronic transformer. Please check that the total lamp wattage does not exceed 75W.
7. Secondary connections must be clean and tight to avoid arcing and overheating!
8. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE SYSTEM

This Package Contains:
Extension Ring - qty. (1)

Extension Ring:

- Begin by separating the canopy cover (B) from the base plate (C), by unscrewing both allen screws (D).

- Then place the canopy cover (B) over the Extension Ring (A) and secure it with the both allen screws (D) located on the side of the base.

- Place the Extension Ring over the mounting plate (C) and secure it with the both allen screws (E) to complete the installation

